

DOXA PLAST | VARNAMO AB

BREDASTENSVAGEN, 19 - 33144 VARNAMO - SVEZIA

E-mail: info@doxaplast.se Telefono: 0046 370 690550 Sito Web Aziendale: <https://www.doxaplastics.com/>



Immagine	Prodotto			Polimero		PSV	
	Totale riciclato	Riciclato post-consumo	Riciclato pre-consumo	Totale Sottoprodotto	Sottoprodotto esterno	Sottoprodotto interno	Materiale vergine
	Stretchfilm - Reused Power			LLDPE		PSV MixEco	
	30%	30%	-	-	-	-	70%
	Dimensioni	- tickness 8 micron. Width 450 ÷ 500 mm. Lenght 300 ÷ 400 m; - tickness 10 micron. Width 450 ÷ 500 mm. Lenght 300 ÷ 400 m; - tickness 20 micron. Width 450 ÷ 500 mm. Lenght 300 ÷ 400 m; - tickness 23 micron. Width 450 ÷ 500 mm. Lenght 300 ÷ 400 m; - tickness 10 micron. Width 500 mm. Lenght 3600 m; - tickness 12 micron. Width 500 mm. Lenght 3000 m; - tickness 15 micron. Width 500 mm. Lenght 2400 m; - tickness 17 micron. Width 500 mm. Lenght 2118 m; - tickness 20 micron. Width 500 mm. Lenght 1740 m; - tickness 23 micron. Width 500 mm. Lenght 1565 m; - tickness 30 micron. Width 500 mm. Lenght 1162 m.					
	Descrizione	Stretchfilm in LLDPE hand applications - Reused Power 8H; - Reused Power 10H; - Reused Power 12H; - Reused Power 15H; - Reused Power 17H; - Reused Power 20H; - Reused Power 23H; machine applications - Reused Power 10M; - Reused Power 12M; - Reused Power 15M; - Reused Power 17M; - Reused Power 20M; - Reused Power 23M; - Reused Power 30M.					
https://www.ippr.it/prodotti/stretchfilm-reused-power/							

Immagine	Prodotto			Polimero		PSV	
	Totale riciclato	Riciclato post-consumo	Riciclato pre-consumo	Totale Sottoprodotto	Sottoprodotto esterno	Sottoprodotto interno	Materiale vergine
	Stretchfilm - Reused Power			LLDPE		PSV MixEco	
	58%	58%	-	-	-	-	42%
	Dimensioni	- tickness 8 micron. Width 450 ÷ 500 mm. Lenght 300 ÷ 400 m; - tickness 10 micron. Width 450 ÷ 500 mm. Lenght 300 ÷ 400 m; - tickness 12 micron. Width 450 ÷ 500 mm. Lenght 300 ÷ 400 m; - tickness 15 micron. Width 450 ÷ 500 mm. Lenght 300 ÷ 400 m; - tickness 17 micron. Width 450 ÷ 500 mm. Lenght 300 ÷ 400 m; - tickness 20 micron. Width 450 ÷ 500 mm. Lenght 300 ÷ 400 m; - tickness 23 micron. Width 450 ÷ 500 mm. Lenght 300 ÷ 400 m; - tickness 10 micron. Width 250 ÷ 500 mm. Lenght 3.600 m; - tickness 12 micron. Width 250 ÷ 500 mm. Lenght 3.000 m; - tickness 15 micron. Width 250 ÷ 500 mm. Lenght 2.322 m; - tickness 17 micron. Width 250 ÷ 500 mm. Lenght 2.118 m; - tickness 18 micron. Width 250 ÷ 500 mm. Lenght 1.954 m; - tickness 19 micron. Width 250 ÷ 500 mm. Lenght 1.895 m; - tickness 20 micron. Width 250 ÷ 500 mm. Lenght 1.800 m; - tickness 23 micron. Width 250 ÷ 500 mm. Lenght 1.514 m; - tickness 30 micron. Width 250 ÷ 500 mm. Lenght 1.162 m					
	Descrizione	Stretchfilm in LLDPE. Machine applications - Reused Power 58 10M; - Reused Power 58 12M; - Reused Power 58 15M; - Reused Power 58 17M; - Reused Power 58 18M; - Reused Power 58 19M; - Reused Power 58 20M; - Reused Power 58 23M; - Reused Power 58 30M. Hand applications - Reused Power 58 8H; - Reused Power 58 10H; - Reused Power 58 12H; - Reused Power 58 15H; - Reused Power 58 17H; - Reused Power 58 20H; - Reused Power 58 23H;					
https://www.ippr.it/prodotti/stretchfilm-reused-power-2/							