

## Intonaci termoisolanti – Termopor CAM 15



### Features

Thermo plaster based on hydraulic binders and expanded polystyrene beads specific for the realization of thermal insulation coatings on external and internal facades. Raw materials are carefully selected and specific additives confer to the product high strength, excellent workability and a diffuse porosity that makes the product highly breathable. The high permeability to water vapor allows the application of the plaster also on damp masonry or affected by capillary rise phenomena, allowing its renovation. Excellent thermal insulation properties, ease of application by machine, excellent dimensional stability guarantee energy saving interventions to perfect regulation of art. Product for professional use. Use: thermal insulation underlayment for energy efficiency of buildings, underlayment, solid bricks, perforated bricks, horizontal bricks, anti-seismic blocks, concrete elements, natural stones, moderately absorbent, mixed masonry of stone and bricks, blocks in tuff, render or cement plaster.

### Dimension

sacchi da 60 L

### Product informations

**Commercial name:** Intonaci termoisolanti - Termopor CAM 15

**Material:** EPS

**PSV MixEco**

| Recycled total | Post-consumer recycled | Pre-consumer recycled | By-product total | External by-product | Internal by-product | Virgin material |
|----------------|------------------------|-----------------------|------------------|---------------------|---------------------|-----------------|
| 15%            | --                     | 15%                   | --               | --                  | --                  | 85%             |

## Producer informations

### **CVR SRL**

Z.I. PADULE - 06024 GUBBIO (PG)

Telephone: 075 9297400

Mail: [giorgio.angeloni@cvr.it](mailto:giorgio.angeloni@cvr.it)

Website: [www.cvr-italy.com](http://www.cvr-italy.com)

March 09, 2023