

## Stretchfilm – Reused Power



### Features

Stretchfilm in LLDPE. Machine applications - Reused Power 58 10M; - Reused Power 58 12M; - Reused Power 58 15M; - Reused Power 58 17M; - Reused Power 58 18M; - Reused Power 58 19M; - Reused Power 58 20M; - Reused Power 58 23M; - Reused Power 58 30M. Hand applications - Reused Power 58 8H; - Reused Power 58 10H; - Reused Power 58 12H; - Reused Power 58 15H; - Reused Power 58 17H; - Reused Power 58 20H; - Reused Power 58 23H;

---

### Dimension

- tickness 8 micron. Width 450 ÷ 500 mm. Lenght 300 ÷ 400 m; - tickness 10 micron. Width 450 ÷ 500 mm. Lenght 300 ÷ 400 m; - tickness 12 micron. Width 450 ÷ 500 mm. Lenght 300 ÷ 400 m; - tickness 15 micron. Width 450 ÷ 500 mm. Lenght 300 ÷ 400 m; - tickness 17 micron. Width 450 ÷ 500 mm. Lenght 300 ÷ 400 m; - tickness 20 micron. Width 450 ÷ 500 mm. Lenght 300 ÷ 400 m; - tickness 23 micron. Width 450 ÷ 500 mm. Lenght 300 ÷ 400 m; - tickness 10 micron. Width 250 ÷ 500 mm. Lenght 3.600 m; - tickness 12 micron. Width 250 ÷ 500 mm. Lenght 3.000 m; - tickness 15 micron. Width 250 ÷ 500 mm. Lenght 2.322 m; - tickness 17 micron. Width 250 ÷ 500 mm. Lenght 2.118 m; - tickness 18 micron. Width 250 ÷ 500 mm. Lenght 1.954 m; - tickness 19 micron. Width 250 ÷ 500 mm. Lenght 1.895 m; - tickness 20 micron. Width 250 ÷ 500 mm. Lenght 1.800 m; - tickness 23 micron. Width 250 ÷ 500 mm. Lenght 1.514 m; - tickness 30 micron. Width 250 ÷ 500 mm. Lenght 1.162 m

---

## Product informations

**Commercial name:** Stretchfilm - Reused Power

**Material:** LLDPE

**PSV MixEco**

Recycled total	Post-consumer recycled	Pre-consumer recycled	By-product total	External by-product	Internal by-product	Virgin material
58%	58%	--	--	--	--	42%

## Productor informations

**DOXA PLAST | VARNAMO AB**

BREDASTENSVAGEN, 19 - 33144 VARNAMO - SVEZIA

Telephone: 0046 370 690550

Mail: [info@doxaplast.se](mailto:info@doxaplast.se)

Website: <https://www.doxaplastics.com/>

May 18, 2023